



SAFETY DATA SHEET

Section 1. Identification of the material and the supplier

Product: **Dinitrol 7250 Spray**
Product Use: Detergent
Restriction of Use: Refer to Section 15

New Zealand Supplier: **Auto Body Equipment**
Address: 17 The Boulevard
Te Rapa, Hamilton, 3200
New Zealand

Telephone: +64 7 849 3514
Email: office@abe.co.nz
Emergency No: 0800 764 766 (National Poison Centre)

Date of SDS Preparation: 5 December 2022

Section 2. Hazards Identification

This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2020

EPA Approval No: Aerosols (Flammable) – HSR002515

Pictograms:



Flammable



Irritant

Signal Word: **DANGER**

GHS Classification and Category	Hazard Code	Hazard Statement
Aerosol Cat. 1	H222	Extremely flammable aerosol.
Aerosol	H229	Pressurised container: may burst if heated.
Eye irritation Cat. 2	H319	Causes serious eye irritation.

Prevention Code	Prevention Statement
P103	Read label before use.
P210	Keep away from heat, sparks, open flames or hot surfaces. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Pressurized container: Do not pierce or burn, even after use.
P264	Wash hands thoroughly after handling.
P280	Wear protective clothing as detailed in Section 8.

Response Code	Response Statement
P305 +	IF IN EYES: Rinse cautiously with water for several minutes. Remove

P351+P338	contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.

Storage Code	Storage Statement
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Disposal Code	Disposal Statement
P501	Dispose of according to Local Regulations or Authorities

Section 3.	Composition / Information on Hazardous Ingredients
-------------------	---

Ingredients	Wt%	CAS NUMBER.
isopropanol (isopropyl alcohol)	12.5 - 20	67-63-0
propane	2.5 - 5	74-98-6
butane	2.5 - 5	106-97-8
isobutane	2.5 - 5	75-28-5
1-methoxy-2-propanol; monopropylene glycol methyl ether	<2.5	107-98-2
Ammonia	<0.5	1336-21-6

Section 4.	First Aid Measures
-------------------	---------------------------

Routes of Exposure:

If in Eyes Rinsing cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.

If on Skin Rinsing skin with water/shower. If skin irritation occurs: get medical advice/attention.

If Swallowed Rinsing mouth. Let water be drunk in little sips (dilution effect). Never give anything to the mouth of an unconscious person. If vomiting occurs, place victim face downwards, with the head turned to the side and lower than the hips to prevent vomit entering the lungs. Call a POISON CENTER or doctor/physician if needed.

If Inhaled Remove person to fresh air. Remove contaminated clothing and loosen remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Apply artificial respiration if not breathing. Get medical advice if breathing becomes difficult.

Most important symptoms and effects, both acute and delayed

Symptoms:

Ingestion: Not applicable.
Inhalation: Not applicable.
Skin: Not applicable.
Eye: Causes serious eye irritation.

Section 5.	Fire Fighting Measures
-------------------	-------------------------------

Hazard Type	Flammable Aerosol
Hazards from products	No data available.
Suitable Extinguishing media	alcohol resistant foam, Carbon dioxide (CO ₂), Extinguishing powder, Water fog. Co-ordinate fire-fighting measures to the fire surroundings. Do not use high power water jet.
Precautions for firefighters and	Wear full protective device. Use water spray jet to protect personnel and to cool endangered containers. Use water spray jet to protect personnel

special protective clothing	and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
HAZCHEM CODE	2YE

Section 6. Accidental Release Measures

Wear protective gear as detailed in Section 8. Evacuate all unnecessary personnel. Avoid contact with skin, eyes and clothes. Remove all sources of ignition. Provide adequate ventilation. Avoid breathing fumes, gas, mist, vapours or spray.

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Dispose of waste according to the applicable local regulations detailed in Section 13.

Section 7. Handling and Storage

Precautions for Handling:

- Read label before use.
- Keep away from heat, sparks, open flames or hot surfaces. No smoking.
- Do not spray on an open flame or other ignition source.
- Pressurized container: Do not pierce or burn, even after use.
- Avoid breathing fumes, mist, vapours or spray.
- Wash hands thoroughly after handling.
- Use only outdoors or in a well-ventilated area. If handled uncovered, arrangements with local exhaust ventilation have to be used.
- If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.
- Take precautionary measures against static discharges.
- Keep away from sources of ignition - No smoking.
- Heating causes rise in pressure with risk of bursting.
- Avoid release to the environment.
- Wear protective clothing as detailed in Section 8.
- Keep away from food, drink and animal feeding stuffs.
- Remove contaminated, saturated clothing immediately.
- When using do not eat or drink.

Precautions for Storage:

- Store away from incompatible materials listed in Section 10.
- Store in a well-ventilated place. Keep container tightly closed in a cool place.
- Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
- Do not keep the container sealed. Keep container dry.
- Keep away from heat. Protect from direct sunlight.

Section 8 Exposure Controls / Personal Protection

WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

Substance		TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
Isopropyl alcohol	[67-63-0]	400	983	500	1230
Butane	[106-97-8]	800	1900	-	-
Propylene glycol monomethyl ether	[107-98-2]	100	369	150	553

Product Name: Dinitrol 7250 Spray
Date of SDS: 5 December 2022

SDS Prepared by: Technical Compliance Consultants (NZ) Ltd
Tel: 64 9 475 5240 www.techcomp.co.nz

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices APRIL 2022 13TH EDITION.

DNEL Values:

CAS No	Substance	Exposure route	Effect	Value
67-63-0	isopropanol (isopropyl alcohol)			
Consumer DNEL, long-term		inhalation	systemic	89 mg/m ³
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	500 mg/m ³

PNEC Values:

CAS No	Substance	Value
67-63-0	isopropanol (isopropyl alcohol)	
Environmental compartment		
Freshwater		140,9 mg/l
Marine water		140,9 mg/l
Freshwater sediment		552 mg/kg
Marine sediment		552 mg/kg
Secondary poisoning		160 mg/kg
Micro-organisms in sewage treatment plants (STP)		2251 mg/l
Soil		28 mg/kg

Engineering Controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Personal Protection Equipment



Eyes	Eye glasses with side protection (EN 166).
Skin	Tested protective gloves must be worn (EN ISO 374): FKM (fluoro rubber), Breakthrough time: 480 min. NBR (Nitrile rubber), Breakthrough time: 240 min. Butyl caoutchouc (butyl rubber) Breakthrough time: 480 min. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Protective gloves have to be replaced at the first sign of deterioration. Protect skin by using skin protective cream. Wear anti-static footwear and clothing.
Respiratory	Work in well-ventilated zones or use proper respiratory protection. gas filtering equipment (EN 141)., Filter material/medium: A2/P3

Section 9 Physical and Chemical Properties

Form	Aerosol
-------------	---------

Colour	Colourless
Odour	Characteristic
Odour Threshold	Not available
pH @20°C	Not available
Boiling Point	Not available
Melting Point	Not available
Freezing Point	Not available
Flash Point	Not available
Flammability	Flammable Aerosol
Upper and Lower Explosive Limits	2.0 Vol% - 12.0 Vol %
Vapour Pressure @20°C	3500 hPa
Density@ 20°C	0.9 g/cm ³
Specific Gravity	Not available
Water Solubility	Completely miscible
Partition Coefficient:	Not available
Ignition Temperature	>425°C
Decomposition Temperature	Not available
Kinematic Viscosity @20°C	Not available
Particle Characteristics	Not available
Solvent content	25.0% water:74.5%
Solids content	0.1

Section 10. Stability and Reactivity

Stability of Substance	This product is stable under normal conditions.
Possibility of hazardous reactions	No hazardous reaction when handled and stored according to provisions.
Conditions to Avoid	Keep away from heat. Ignition hazard.
Incompatible Materials	None known.
Hazardous Decomposition Products	No dangerous decomposition products known.

Section 11 Toxicological Information

Acute Effects:

Swallowed	Not applicable.
Dermal	Not applicable.
Inhalation	Not applicable.
Eye	Causes serious eye irritation.
Skin	Not applicable.

Chronic Effects:

Carcinogenicity	Not applicable.
Reproductive Toxicity	Not applicable.
Germ Cell Mutagenicity	Not applicable.
Aspiration	Not applicable.
STOT/SE	Not applicable.
STOT/RE	Not applicable.

Acute Toxicity for components:

CAS No	Chemical name
--------	---------------

	Exposure route	Dose	Species	Source	
67-63-0	isopropanol (isopropyl alcohol)				
	oral	LD50 mg/kg	4570	Rat	
	dermal	LD50 mg/kg	13400	Rabbit	
	inhalation (4 h) vapour	LC50	30 mg/l	Rat	
106-97-8	butane				
	inhalation (4 h) gas	LC50 ppm	273000	Rat	GESTIS
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether				
	oral	LD50 mg/kg	> 5000	Rat	IUCLID
	dermal	LD50 mg/kg	>2000	Rabbit	

Section 12. Ecotoxicological Information

Not known to be hazardous to the environment.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether					
	Acute fish toxicity	LC50 10000 mg/l	4600 -	96 h	Leuciscus idus	IUCLID
	Acute algae toxicity	ErC50 mg/l	> 1000	72 h	Selenastrum capricornutum	
	Acute crustacea toxicity	EC50 mg/l	> 500	48 h	Daphnia magna	IUCLID

Persistence and Degradability:

No data for the product itself

Bioaccumulative Potential:

No data for the product itself

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	isopropanol (isopropyl alcohol)	0,05
106-97-8	butane	2,89
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether	-0,437
1336-21-6	Ammonia	-1,38

Mobility in Soil:

No data available for the product itself.

Section 13. Disposal Considerations

Disposal Method:

Spent media that has removed toxic chemicals should be examined for specific hazards. Spilled product may be recovered for use if it has not come in contact with liquids or been exposed to significant amounts of gaseous contaminants. Dispose of according to Local Regulations.

Ensure any container holding waste product or contaminated spill media is labelled "Hazardous Waste - "Spilled Flammable Aerosol" and that the label also has the Flammable Pictogram, and the business name, address, and phone number.

Precautions or methods to avoid: Must not be disposed together with household garbage. Avoid release to the environment.

This product is classified as a Dangerous Good for transport in NZ ; NZS 5433:2020



Road and Rail Transport

UN No: 1950
 Class-primary: 2
 Proper Shipping Name: AEROSOLS

Air Transport

UN No: 1950
 Class-primary: 2
 Proper Shipping Name: AEROSOLS

Marine Transport

UN No: 1950
 Class-primary: 2
 Proper Shipping Name: AEROSOLS
 Marine Pollutant: No

Special Provisions: 63, 190, 277, 344, 327

Limited Quantity: For aerosols containing toxic substances the limited quantity is 120ml. For all other aerosols the limited quantity is 1000ml.

Section 15

Regulatory Information

New Zealand:

This substance is classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2020

EPA Approval Code: Aerosols (Flammable) – HSR002515

HSW (HS) Regulations 2017 and EPA Notices	Trigger Quantity
Certified Handler	Not required
Location Certificate	3000L (AWC)
Tracking Trigger Quantities	Not required
Signage Trigger Quantities	3000L (AWC)
Emergency Response Plan	3000L (AWC)
Secondary Containment	3000L (AWC)
Fire Extinguishers	3000 (AWC) - require 1X
Restriction of Use	Only use for the intended purpose.

Section 16

Other Information

Glossary

EC ₅₀	Median effective concentration.
EEL	Environmental Exposure Limit.
EPA	Environmental Protection Authority
HSNO	Hazardous Substances and New Organisms.
HSW	Health and Safety at Work.
LC ₅₀	Lethal concentration that will kill 50% of the test organisms inhaling or ingesting it.
LD ₅₀	Lethal dose to kill 50% of test animals/organisms.
LEL	Lower explosive level.
OSHA	American Occupational Safety and Health Administration.
TEL	Tolerable Exposure Limit.
TLV	Threshold Limit Value-an exposure limit set by responsible authority.
UEL	Upper Explosive Level

References:

1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
2. Workplace Exposure Standards and Biological Exposure Indices April 2022 edition.
3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
4. Transport of Dangerous goods on land NZS 5433:2020
5. HSW (Hazardous Substances) Regulations 2017

Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact Auto Body Equipment, if further information is required.

Issue Date:

5 December 2022

Review Date:

5 December 2027