

Colad Scuff Rolls

The high quality Scuff Rolls are especially designed for both manual or machine use. Prior to applications of finishing coat, primer or lacquer. Can be used on painted surfaces, but also on plastics, wood and metal surfaces.

Type A, Very Fine, is particularly appropriate for the roughening of unpainted or primed plastics, plywood steel and aluminum parts. Scuff Discs may also be used to prepare new sheet metal parts for refinishing. Type S, Ultra Fine, is particularly effective for the roughening between coats, when using 2 component paints and primers. This Scuff Disc may be used to repair blend areas.

Benefits of Scuff Rolls:

- Long lifetime
- Can be used wet and dry
- Easy to shape and fold, while maintaining the effectiveness due to three-dimensional fiber structure
- High abrasion capacity
- Gives an excellent smooth finish
- Ideal for matting of surfaces and creates an excellent base for the next lacquer layer
- Can be used on painted surfaces, but also on unpainted wood, plastics and metal surfaces. Substrate range: Paints, Coatings, Steel and stainless steel , Plastics , Copper alloys / brass / bronze , Primers, Plywood , Aluminum , Etc.



Article number: 3820xx00

Description: Scuff Rolls



Art no.	Variant	EAN
38200800	Very Fine	8714247000311
38201500	Ultra Fine	8714247000328

Packaging information

1 roll shrink wrapped

Technical information

- Width: 115 mm
- Roll length: 10 meters
- Backing: Non-woven
- Grain: Aluminum Oxide (VF) and Silicon carbide (UF)
- Bonding: Resin
- Coating: Three-dimensional

Frequently Asked Questions

> Where can I use the Scuff Rolls for?

Use on flat, irregular, or contoured surfaces. Ideal for matting of surfaces and creates an excellent base for the next lacquer layer.

> For which industries are Scuff Rolls suitable?

- Car body repairs
- Vehicle production
- Ship and yacht building
- Metal processing
- Decoration and construction
- Wood processing

> What is the difference between the Red and Grey color?

Red, is particularly appropriate for the roughening of unpainted plastics, plywood and aluminum.

Grey, is particularly effective for the roughening between coats, when using 2 component paints and primers.

Related products



3850xx00

Scuff Discs



3800xx00

Scuff Pads



120xx0

Sandpaper Roll



38951xx0

Soft Flex Rolls



17 The Boulevard
Te Rapa, Hamilton
New Zealand

Ph: 07 849 3514
Email: office@abe.co.nz
Web: www.abe.co.nz

Disclaimer

It is the responsibility of the user to read, understand and apply the information contained in this data sheet. Products are for professional use only. Necessary protective equipment and clothing should be worn. Repairs should always be done in accordance with OEM guidelines and regulations. All information is for the user's consideration, investigation and verification. The specific use, application and conditions of use are beyond the control of EMM International BV. It is the responsibility of the user to determine the suitability of the product for the user's specific application.